

MANUFACTURERS AND SUPPLIERS OF

BLACK AND COLOURED IRON OXIDES

POWDER
GRANULAR
LIQUID COLOUR

FLOOR COATINGS

OVERLAY
CEMCOTE
COLOUR HARDENER
CHEMICAL STAIN
MICRO TOPPING

WALL COATINGS

CEMPAINT
MICRO COLOUR
FIBRECOTE
DECOCRETE

CONCRETE ADMIXTURES

ACTIVATOR

SEALERS

SOLVENT
EPOXY
URETHANE
WATER BASED
LOW ODOUR
MATTING AGENTS
TINTED SEALERS
DENSIFIERS
SILICONE BASED

STAMPED CONCRETE MATS

SEAMLESS
TIMBER
SLEEPER
STONE & BLOCK PATTERNS
STENCILS

ADDITIVES

WATERPROOFING
PLASTICIZING AGENTS
FIBRES
ACCELERATORS
HARDENERS
EFFLORESCENCE CONTROL AGENTS

ANTISLIP ADDITIVES

GLASS GRIT
SLIP REDUCER

CONCRETE TOOLS

TROWELS
SCREEDS
FLOATS
BROOMS
ROLLERS
CONFORM BOXING
SAFETY NETS
ELECTRIC & PUMP SPRAYERS
GRINDING AND CUTTING DISCS

EQUIPMENT HIRE

GRINDER
VACUUM

SAFETY GEAR

HI VIZ VESTS AND JACKETS
SAFETY BOOTS
GLASSES

HEAD OFFICE 42a Egmont Road, PO Box 7022, New Plymouth,
06 755 3320, info@permacolour.co.nz

FREEPHONE 0508 444 555

AUCKLAND WAREHOUSE Unit 4-16 Zelanian Drive, East Tamaki, Auckland,
09 272 8444, auckland@permacolour.co.nz

FREEPHONE 0508 666 777

CHRISTCHURCH OFFICE 23 Watts Road, Sockburn,
PO Box 39148, Harewood, Christchurch
03 358 9669, christchurch@permacolour.co.nz



New Zealand Decorative Concrete Supplies

is a private company, 100% New Zealand owned and operated, providing the highest quality products and service in the decorative concrete industry!

Micro Colour

JUNE 2022

Permacolour Micro Colour is a thin cement based decorative plaster that creates a smooth, coloured mottled finish for interior wall surfaces only and can be applied to masonry or previously painted surfaces.



Micro Colour

DESCRIPTION

Permacolour Micro Colour is a thin cement based decorative plaster that creates a smooth, coloured mottled finish for interior wall surfaces only and can be applied to masonry or previously painted surfaces.

PURPOSE

Permacolour Micro Colour is designed to provide a durable, attractive wall covering for new and existing surfaces. It is versatile, easy to apply, requires minimal maintenance and is an aesthetically pleasing alternative to paint, wall paper and other conventional finishes.

SPECIFYING

Apply Permacolour Micro Colour in an approved colour to wall surfaces, by trowel all in accordance with the manufacturers specifications.

WEATHER

This product is best applied at temperatures between 5 and 30 degrees. Do not apply under conditions where there is excessive air movement or draught.

SUITABLE SURFACES

- For internal use only.
- Good, clean concrete, masonry and fibrous cement surfaces.
- Primed or painted Gib board.

SURFACE PREPARATION

All surfaces should be firm, clean and free from loose adhering particles, and any contaminants that may impair adhesion.

MIXING

Whilst stirring at a slow speed with an electrical mixer, slowly add 10kg of Micro Colour powder to 4.6 litres of clean water and continue mixing until a smooth lump free consistency has been achieved. Allow to stand for 4 minutes and remix for 1 minute.

If non-standard colours are being used, add 1 x 300 gram sachet of colour to the water first and mix thoroughly before adding 10kg of Permacolour Micro Colour powder.

APPLICATION

Prime the surfaces with a solution of 1 part Permacolour Activator and 1 part water, by brush or roller. Two coats of primer may be required depending on the suction of the substrate.

Allow the primer to dry, then trowel down the mix quickly and evenly across the surface, removing most of the trowel marks. Allow the material to reach an initial set, then flick or spray a small amount of water and trowel smooth, removing all blemishes or trowel marks. The completed wall should be left overnight to dry and lightly sanded on the day following application using 150 grit paper.

Remove all dust from the sand papering process with water and a sponge. Ensure all dirty water is removed from the surface.

COLOURS

- Available in eight standard colours.
- For additional colours, use colour packs with white or grey bases.

SEALING

The dry, cured surface can be sealed using Permacolour Stone Sheen or Repell SS, dependent on the desired finish. Apply sealer as specified.

COVERAGE

20m² per 10kg bag at 0.5mm thick.

Coverage depends largely on the experience of the contractor to trowel thin and evenly as well as the surface texture of the substrate.

PACKAGING:

Micro Topping: 10kg non-returnable paper bags.

Colour Packs: 300gram sachets

PRODUCT INFORMATION SHEET

SHELF LIFE

Unopened bags can be stored in a dry shed off the floor on wooden slats for 12 months.

DISCLAIMER

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

As all Permacolours technical data sheets are updated on a regular basis, it is the users responsibility to obtain the most recent issue.

CONDITIONS OF SALE

The material is guaranteed to be of standard quality and to conform to our published specifications. Since we have no control over use and application of this material, nor the areas to which it is applied, we disclaim any and all responsibility or warranties, expressed or implied, in connection with it's use, handling and storage or the results obtained; as well as any injury, damage of any nature whatsoever, resulting from its uses.



			
SILVERSAND	IRONSIDE	SERENGETI	OLIVE
			
RICOCHET	BLACK	STARBURST	WASABI
			
CONCORD	CORK	WHEAT	AMAZON
			
DUNE	LUMBERJACK	OATMEAL	SEAWEED
			
HESSIAN	BURNT UMBER	CHATEAU	RIVERSTONE
			
BALI	MANDERIN	PEARL	GLACIA
			
PULSE	FARRENHEIT	BUBBLEGUM	PHANTOM