

PRODUCT DESCRIPTION

Permacolour Release Agent is a specially formulated coloured powder designed to insure that the finest details of polyurethane texturing mats are transferred accurately to freshly placed coloured concrete. Permacolour Release Agent will greatly aid finishing by preventing freshly placed concrete from adhering to the texturing mats.

APPLICATION INSTRUCTIONS

Before applying Permacolour Release Agent, protect all surrounding areas where colour is not desired. The release powder may be applied to the surface of the freshly placed concrete as soon as all standing water has disappeared from the concrete surface. Usually the concrete has at least a "Fresno" or "walking trowel" finish. If Permacolour Hardener has been applied, the finishing will be more extensive. Apply Permacolour Release Agent in a broadcasting fashion until a thin uniform layer covers the concrete surface to be textured. Application of texturing mats may begin as soon as Permacolour Release Agent has been applied. Permacolour Release Agent should be removed from the concrete surface when removal can be safely accomplished without any damage to the curing concrete surface, (usually 3 to 4 days after imprinting). Excess release agent may be swept from the slab. Residual Permacolour Release Agent may be removed to a degree desired using a high pressure washer, by scrubbing or buffing, taking care not to damage the curing coloured concrete surface. The amount of release agent adhering to the concrete surface will depend upon how hard the concrete surface was at the time of application and texturing. A softer concrete surface will retain more release agent colour than a harder concrete surface.

COVERAGE

The rate will vary depending upon the depth of the texturing mat impressions desired and the degree to which the concrete has set. 10kg per 70 to 80 square metres or more may be required.

NOTE

Always fluff up release agent before using by shaking container, this will increase coverage.

PACKAGING

10kg pack.

WARRANTY

Permacolour products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. The information contained herein is true and accurate to the best knowledge of Permacolour. Since we cannot anticipate all possibilities and conditions under which this information and our products may be used, Permacolour hereby accepts no responsibility and offers no warranty in the case of results achieved by the use of our products or of the safe use and suitability of these products. Permacolour offers our products for sale subject to, and "The Customer" and all users are deemed to have accepted our Terms and Conditions of Sale. We warrant our products to be free of manufacturing defects. If any product is found to be defective and was within storage/shelf life, Permacolour will replace the product at no charge to the purchaser. Permacolour makes no other warranty with regards to our products, either expressed or implied. Whilst any information provided by ourselves, both verbally or written, is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. As all Permacolour technical data sheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.