

## **LIQUID RELEASE AGENT**

PERMACOLOUR Liquid Release is a parting agent used to keep texturing mats from sticking to the still plastic concrete. It also prolongs the life of the texturing mat by decreasing the friction between the texturing mat and the concrete. It forms a lubricating and parting barrier separating the concrete from the texturing mat.

Permacolour Clear Liquid Release Agent comes in 5, 10, 20 & 200 ltr containers.

Permacolour Coloured Liquid Release Agent comes 5 & 10ltr containers.

**INSTRUCTIONS:** Using a pump type sprayer, apply a mist of Permacolour Clear Liquid Release onto the Imprinting Mats that you are going to use to keep them lubricated. Re-apply as necessary.

When spraying on a surface that is going to be Imprinted, only mist the concrete surface, Do not over apply as this can cause a stippling effect on the imprinted surface.

Using a pump type sprayer, apply a mist of Permacolour Clear Liquid Release on the coloured concrete where you are going to place the next few stamping mats. Do not apply over an area of more than three or four square metres as the Permacolour Liquid Release may evaporate before the mats are placed over it.

At this stage when you lift the mats you may apply a coloured liquid release agent to achieve a quality antiquing effect. Mist newly imprinted area with desired colour then use the trowel as if using a squeegee, pull trowel across surface to drag excess coloured release agent from high points to low area's. This technique gives best results with little or no smudging.

Alternatively on larger areas imprint with clear liquid release agent and colour wash the following day.

To maintain the integrity of the Colour Hardened surface, do not trowel, or, in any way, mix the Permacolour Liquid Release with the surface. To make corrections on the still plastic concrete, use the texturing tool or skins and press out the unwanted impression.

**COVERAGE:** Permacolour Liquid Release covers approximately 10-12m<sup>2</sup> per litre.

**SEALING:** Once the concrete surface is dry & hard enough to walk on, a coat of Permacolour Sealer Primer can be applied. Perma-Colour Sealer Primer can be applied immediately over the Perma-Colour Liquid Release. No removal of the Liquid Release is necessary. When stamping is completed, wash off the Perma-colour Liquid Release from the texturing mats using concrete cleaner with water. Leave for 5-7 days then seal with Perma- Colour Concrete sealer.

**WARNING:** COMBUSTIBLE, KEEP AWAY FROM HEAT AND OPEN FLAME. CLOSE CONTAINER AFTER EACH USE. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. FOR PROFESSIONAL USE ONLY.

In all cases of suspected poisoning, seek medical aid at once. If swallowed, DO NOT induce vomiting. Give 250ml water to drink. DO NOT give anything by mouth to an unconscious person. If vapour has been inhaled, remove affected person to fresh air and obtain medical attention in severe cases.

**LIMITED WARRANTY:** These products are warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over their use, no warranty, expressed or implied, is made as to the effect of such use. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material to be defective.

**NEW PLYMOUTH BRANCH**

42a Egmont Road,  
PO Box 7022, New Plymouth  
06 755 3320  
info@permacolour.co.nz  
**FREEPHONE 0508 444 555**

**AUCKLAND BRANCH**

Unit 4, 16 Zelanian Drive,  
East Tamaki, Auckland  
09 272 8444  
auckland@permacolour.co.nz  
**FREEPHONE 0508 666 777**

**CHRISTCHURCH BRANCH**

25a Sheffield Crescent,  
Burnside, Christchurch  
03 358 9669  
christchurch@permacolour.co.nz  
**PHONE 03 358 9669**



**New Zealand's Largest and Most Experienced Manufacturer and Supplier of**

CONCRETE COLOURINGS | IMPRINTING & OVERLAY PRODUCTS & EQUIPMENT | CONCRETE TOOLS

CONCRETE COATINGS & ADDITIVES | OXIDES & SEALERS | TRAINING

**[www.permacolour.co.nz](http://www.permacolour.co.nz)**