

PRODUCT DESCRIPTION

Permacolour Liquid Release Agent is a parting agent used to keep texturing mats from sticking to the still plastic concrete. It also prolongs the life of the texturing mat by decreasing the friction between the texturing mat and the concrete. It forms a lubricating and parting barrier separating the concrete from the texturing mat.

APPLICATION INSTRUCTIONS

Using a pump type sprayer, apply a mist of Permacolour Clear Liquid Release onto the Imprinting Mats that you are going to use to keep them lubricated. Re-apply as necessary. When spraying on a surface that is going to be Imprinted, only mist the concrete surface. Do not over apply as this can cause a stippling effect on the imprinted surface. Using a pump type sprayer, apply a mist of Permacolour Clear Liquid Release on the coloured concrete where you are going to place the next few stamping mats. Do not apply over an area of more than three or four square metres as the Permacolour Liquid Release may evaporate before the mats are placed over it. At this stage when you lift the mats you may apply a coloured liquid release agent to achieve a quality antiquing effect. Mist newly imprinted area with desired colour then use the trowel as if using a squeegee, pull trowel across surface to drag excess coloured release agent from high points to low area's. This technique gives best results with little or no smudging. Alternatively on larger areas imprint with clear liquid release agent and colour wash the following day. To maintain the integrity of the Colour Hardened surface, do not trowel, or, in any way, mix the Permacolour Liquid Release with the surface. To make corrections on the still plastic concrete, use the texturing tool or skins and press out the unwanted impression.

COVERAGE

Permacolour Liquid Release covers approximately 10-12m² per litre.

PACKAGING

5 & 20 litre packs.

SEALING

Once the concrete surface is dry & hard enough to walk on, a coat of Permacolour Sealer Primer can be applied. Permacolour Sealer Primer can be applied immediately over the Perma-Colour Liquid Release. No removal of the Liquid Release is necessary. When stamping is completed, wash off the Perma-colour Liquid Release from the texturing mats using concrete cleaner with water. Leave for 5-7 days then seal with Permacolour Concrete sealer.

WARNING

COMBUSTIBLE, KEEP AWAY FROM HEAT AND OPEN FLAME. CLOSE CONTAINER AFTER EACH USE. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. FOR PROFESSIONAL USE ONLY.

In all cases of suspected poisoning, seek medical aid at once. If swallowed, DO NOT induce vomiting. Give 250ml water to drink. DO NOT give anything by mouth to an unconscious person. If vapour has been inhaled, remove affected person to fresh air and obtain medical attention in severe cases.

LIMITED WARRANTY

These products are warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over their use, no warranty, expressed or implied, is made as to the effect of such use. Seller's and Manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material to be defective.

WARRANTY

Permacolour products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. The information contained herein is true and accurate to the best knowledge of Permacolour. Since we cannot anticipate all possibilities and conditions under which this information and our products may be used, Permacolour hereby accepts no responsibility and offers no warranty in the case of results achieved by the use of our products or of the safe use and suitability of these products. Permacolour offers our products for sale subject to, and "The Customer" and all users are deemed to have accepted our Terms and Conditions of Sale. We warrant our products to be free of manufacturing defects. If any product is found to be defective and was within storage/shelf life, Permacolour will replace the product at no charge to the purchaser. Permacolour makes no other warranty with regards to our products, either expressed or implied. Whilst any information provided by ourselves, both verbally or written, is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. As all Permacolour technical data sheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.